

Sentry Smart CDU

Key Features

- > High Density: 24 outlets per enclosure (18) 208V IEC C13, (6) 208V IEC C19 outlets and (1) 120V NEMA 5-20R accessories outlet
- > Power Distribution: 208-240 3-Phase Delta and Wye 20/30A power infeed options.
- > Input Current Monitor: Precisely measure the aggregate current draw (in amps) of the circuit. On-site verification of the input current with LED digital display. Remote verification via web browser or serial screen.
- > IP Access & Security: Web interface, SSL, SSH, Telnet, SNMP, FTP, SNT, Syslog, LDAP, LDAPS, TACACS, RADIUS, and RS-232 access
- > SNMP Traps and Email alerts: Provide automated alerts for power and environmental conditions
- > Environmental Monitoring: Each Smart CDU supports two external temperature & humidity probes and reports conditions thru the user interface without the need for additional IP addresses
- > Add an Expansion Module: Connect the Smart Expansion CDU (CLG) to a Master unit (CSG) for power monitoring of separate power circuits from a single IP address

CSG-24VY 20/30A Smart POPS™ with Mixed Outlet

High-Density Power Distribution

The Smart Cabinet Power Distribution Units (CDU) provide reliable power distribution combined with local and remote power monitoring and environmental monitoring via IP. Use the network interface to view power, temperature and humidity levels via Web browser, or receive SNMP-based alarms and email alerts when conditions exceed defined thresholds.

Sentry POPS (Per Outlet Power Sensing) combines all of the features and functions of a Smart CDU with the ability to provide power monitoring per an individual outlet/device. Power information per individual outlet/device includes current, voltage, power (kW), apparent power, crest factor, and power factor. Using out grouping technology, power information is available per device, groups of devices (application), individual CDU or cabinet.

Additional Benefits:



POPS™ (Per Outlet Power Sensing)

Monitor Current Load (A), Voltage (V), Power (W), Apparent Power (VA), Crest Factor and Power Factor per outlet at an accuracy of $\pm 2\%$.



Branch Circuit Protection

The Sentry CDU Family meets the UL 60950-1 requirement for Branch Circuit Protections
> UL-489 rated circuit breakers



PIPS - Per Input Power Sensing

Accurately measures Active Power, Apparent Power, Energy k-Wh, Power Capacity, and Power Capacity Used using the network interface. See the aggregate current draw, in Amps, locally using the onboard LED.



Temperature and Humidity

The Smart CDU supports two external 10ft (3m) probes. Each of these probes measure both temperature and humidity. Receive SNMP-based alerts or email notifications when conditions exceed defined thresholds.



Mixed Outlets

This Smart CDU combines 18 IEC 60320 C13 and 6 IEC 60320 C19 outlets within a single CDU to monitor power at the outlet-level.



Wye unit with 120V NEMA Utility Outlet Shown

Model	Available Input Voltages	Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
CSG-24VDD425A1 CLG-24VDD425A1*	240V 3-phase Delta 50/60Hz	20A	NEMA L15-20P Plug, 10'(3m) Bottom/Frt Cord	(18) IEC 60320/C13 (6) IEC 60320/C19	69.0 x 1.75 x 3.50 in. (1753 x 44 x89 mm)
CSG-24VDE425A1 CLG-24VDE425A1*	240V 3-phase Delta 50/60Hz	30A	NEMA L15-30P Plug, 10'(3m) Bottom/Frt Cord	(18) IEC 60320/C13 (6) IEC 60320/C19	69.0 x 1.75 x 3.50 in. (1753 x 44 x89 mm)
CSG-24VYL425C9 CLG-24VYL425C9*	208V 3-phase Wye 50/60Hz	20A	NEMA L21-20P Plug, 10'(3m) Bottom/Frt Cord	(18) IEC 60320/C13** (6) IEC 60320/C19	69.0 x 1.75 x 3.50 in. (1753 x 44 x89 mm)
CSG-24VYM425C9 CLG-24VYM425C9*	208V 3-phase Wye 50/60Hz	30A	NEMA L21-30P Plug, 10'(3m) Bottom/Frt Cord	(18) IEC 60320/C13** (6) IEC 60320/C19	69.0 x 1.75 x 3.50 in. (1753 x 44 x89 mm)

* CLG part numbers refer to the Expansion CDU

** Product has unmonitored NEMA 5-20R accessories outlet

Additional Features and Specifications

Agency Approvals

- > US & Canada (cTUVus Mark) to UL 60950-1: 2007 and CAN/CSA 22.2 No. 60950-1-07
- > FCC Class A, Part 15
- > EMC to EN 55022 Class A, EN 55024, CISPR 22 Class A

Communications and Security

- > 10/100 BaseT Ethernet
- > HTTP/HTTPS
- > SSLv3/TLSv1
- > SNMPv2 and v3
- > SSHv2
- > Telnet
- > LDAPS/LDAPv3
- > TACACS+
- > RADIUS
- > RS-232 (Serial)
- > IPv4 and v6

Branch Circuit Protection

- > Compliant to UL 60950-1

Accessories

- > Optional Temperature & Humidity Probe
 - EMTH-1-1 Temperature & Humidity Probe, 10 ft (3m)
- > Environmental Monitor
 - EMCU-1-1B allows up to (2) additional temperature & humidity probes, (1) water sensor, (4) dry contact closures, (1) analog-to-digital contact sensor. Includes (1) temperature/humidity probe with unit.
- > SPM (Sentry Power Manager):
 - Monitor and Manage multiple Sentry CDU's
 - Monitor and Manage all alarm conditions
 - Reporting and Trending
 - Group or Cluster outlets for reboot and power information
 - Optional Appliance or virtual version
 - SPM v5.1+ is vmware READY



VMware and VMware Ready is a registered trademark or trademark of VMware, Inc. in the United States and/or other jurisdictions

1U SPM Appliance



Expansion Module Model Numbers

- > CLG-24VDD425A1
- > CLG-24VDE425A1
- > CLG-24VYL425C9
- > CLG-24VYM425C9



Server Technology

HEADQUARTERS - NORTH AMERICA

Server Technology, Inc.
1040 Sandhill Drive
Reno, NV 89521
United States
1.775.284.2000 Tel
1.775.284.2065 Fax
sales@servertech.com
www.servertech.com
www.servertechblog.com

Western Europe, Middle East and Africa

Fountain Court
2 Victoria Square
Victoria Street
St. Albans
AL1 3TF
United Kingdom
+44 (0) 1727 884676 Tel
+44 (0) 1727 220815 Fax
salesint@servertech.com

Central Europe, Eastern Europe and Russia

Niederlassung Deutschland
Server Technology LLC
42119 Wuppertal
Germany
Tel: + 49 202 693917 x 0
Fax: + 49 202 693917-10
salesint@servertech.com

APAC

37th Floor
Singapore Land Tower
50 Raffles Place
Singapore 048623
Phone: +65 9739.0396
Fax: +65 6234.4574
salesint@servertech.com