



INSTALLATION

1. The cable manager can be mounted on the left or right side of the cabinet and can either be positioned towards the front of the cabinet, as shown in Figure 1, or face the rear of the cabinet. Two cable managers can be mounted on each side of 24" and 30" deep cabinets, only one can be mounted in 18" deep cabinets.
2. The manager must be installed prior to equipment being installed on the rails.


**Figure 1**

The door, rear panel, top and side panels are not shown for clarity


3. Position the manager in the side of the cabinet so that it is between the top and bottom horizontal slides and up against the side panel. The plastic cable guides should be towards the center of the cabinet.



4. Move the wing nuts in the slides towards the center.



5. Extend the brackets on the cable manager by loosening the two wing nuts and sliding the bracket towards the end completely, retighten the wing nuts.



6. Slide the wing nut into the bracket slot and position the manager in the desired location, tighten the wing nut.

CPI CHATSWORTH PRODUCTS, INC.

800-834-4969 techsupport@chatsworth.com www.chatsworth.com

**INSTALLATION INSTRUCTIONS,
CABLE MANAGER,
CUBE IT CABINET**

THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO CHATSWORTH PRODUCTS, INC. ANY REPRODUCTION DISCLOSURE OR USE OF THIS DRAWING IS EXPRESSLY FORBIDDEN EXCEPT AS AGREED TO IN WRITING BY CHATSWORTH PRODUCTS, INC.